



RT-MP-4F-65

4.0x Telecentric lens with built-in coaxial illumination for detectors up to 1"

SPECIFICATIONS

Optical specifications


Magnification		4
Image circle Ø	(mm)	16
Max detector size		1"
Working distance	(mm)	65
wF/# 1		16.7
Distortion	(%)	0.23
Field depth	(mm)	0.044
Nominal resolving power	(µm)	2.8

Object field of view

with 1/3" detector (4.8 x 3.6 mm)	(mm x mm)	1.2 x 0.9
with 1/2.5" detector (5.70 x 4.28 mm)	(mm x mm)	1.4 x 1.1
with 1/2" detector (6.4 x 4.8 mm)	(mm x mm)	1.6 x 1.2
with 1/1.8" detector (7.13 x 5.37 mm)	(mm x mm)	1.8 x 1.3
with 2/3" - 5 MP detector (8.45 x 7.07 mm)	(mm x mm)	2.1 x 1.8
with KAI-04050 16 mm diagonal w x h 12.8 x 9.6	(mm x mm)	3.2 x 2.4

Mechanical specifications

Mount		C
Length	(mm)	165.5
Diameter	(mm)	29
Mass	(g)	150
Focus lock screws		-
Iris lock screws		-



NOTES

- Working distance: distance between the front end of the mechanics and the object. Set this distance within +/- 3% of the nominal value for maximum resolution and minimum distortion.
- F/# = F-number, wF/# = working F-number, the real F-number of a lens when used as a macro.

COMPATIBLE PRODUCTS



LT2RZF050-60-2-W-24V	LED ringlight, 2 LED rows, 50.8 mm outer diameter, 60°, white, 24V
LT2RZF050-60-2-R-24V	LED ringlight, 2 LED rows, 50.8 mm outer diameter, 60°, red, 24V
LT2RZF050-60-2-G-24V	LED ringlight, 2 LED rows, 50.8 mm outer diameter, 60°, green, 24V
LT2RZF050-60-2-B-24V	LED ringlight, 2 LED rows, 50.8 mm outer diameter, 60°, blue, 24V



LTZZO130-75-3-W-24V	LED low angle ringlight, 3 LED rows, outer diameter 131 mm, 75°, white, 24V
LTZZO130-75-3-R-24V	LED low angle ringlight, 3 LED rows, outer diameter 131 mm, 75°, red, 24V
LTZZO130-75-3-G-24V	LED low angle ringlight, 3 LED rows, outer diameter 131 mm, 75°, green, 24V
LTZZO130-75-3-B-24V	LED low angle ringlight, 3 LED rows, outer diameter 131 mm, 75°, blue, 24V



LTZGK050-15-2-W-24V	LED ringlight, 2 LED rows, outer diameter 50 mm, 15°, white, 24V
LTZGK050-15-2-R-24V	LED ringlight, 2 LED rows, outer diameter 50 mm, 15°, red, 24V
LTZGK050-15-2-G-24V	LED ringlight, 2 LED rows, outer diameter 50 mm, 15°, green, 24V
LTZGK050-15-2-B-24V	LED ringlight, 2 LED rows, outer diameter 50 mm, 15°, blue, 24V

LTZGK070-45-3-W-24V	LED ringlight, 3 LED rows, outer diameter 70 mm, 45°, white, 24V
LTZGK070-45-3-R-24V	LED ringlight, 3 LED rows, outer diameter 70 mm, 45°, red, 24V
LTZGK070-45-3-G-24V	LED ringlight, 3 LED rows, outer diameter 70 mm, 45°, green, 24V
LTZGK070-45-3-B-24V	LED ringlight, 3 LED rows, outer diameter 70 mm, 45°, blue, 24V



LTPVRG25X36-00-1-W-24V	Flat side-emitting LED backlight, thin borders, 25X36 mm illumination area, white, 24V
LTPVRG25X36-00-1-R-24V	Flat side-emitting LED backlight, thin borders, 25X36 mm illumination area, red, 24V
LTPVRG25X36-00-1-G-24V	Flat side-emitting LED backlight, thin borders, 25X36 mm illumination area, green, 24V
LTPVRG25X36-00-1-B-24V	Flat side-emitting LED backlight, thin borders, 25X36 mm illumination area, blue, 24V



LTZPFL040-00-6-W-24V	LED bar light, 6 LED rows, 40X26.3 illumination area, white, 24V
LTZPFL040-00-6-R-24V	LED bar light, 6 LED rows, 40X26.3 illumination area, red, 24V
LTZPFL040-00-6-G-24V	LED bar light, 6 LED rows, 40X26.3 illumination area, green, 24V
LTZPFL040-00-6-B-24V	LED bar light, 6 LED rows, 40X26.3 illumination area, blue, 24V