

# TCCR12120

Bi-telecentric CORE lens for 1/2" detectors, magnification 0.052 x, C-mount

## SPECIFICATIONS

Part number (8)		TCCR12120
Magnification	(x)	0.052
Image shape dimension (9)	( $\varnothing$ , x mm)	$\varnothing=8.2$ , x=6.7
Phase adjustment (7)		Yes

### Object field of view (6)

with 1/3" detector (4.8 x 3.6 mm)	(mm x mm)	92.1 x 69.1
with 1/2.5" detector (5.70 x 4.28 mm)	(mm x mm)	109.4 x 82.0
with 1/2" detector (6.4 x 4.8 mm)	(mm x mm)	122.8 x 92.1
with 1/1.8" detector (7.13 x 5.37 mm)	(mm x mm)	128.0 x 103.3
with 2/3" - 5 MP detector (8.45 x 7.07 mm)	(mm x mm)	$\varnothing=157$ , x=128

### Optical specifications

Working distance (1)	(mm)	334.5
wF/# (2)		8
Telecentricity typical (max) (3)	(deg)	< 0.06 (0.08)
Distortion typical (max) (4)	(%)	< 0.08 (0.10)
Field depth (5)	(mm)	247
CTF @ 70 lp/mm	(%)	> 45

### Dimensions

Mount		C
A	(mm)	182
B	(mm)	220
C	(mm)	231
Mass	(g)	9127

### Compatibility

LTCLCR096-x, CMHOCR096, CMPTR096, LTCLHP096-x

**In case of use with sensors larger than 1/1.8" please check the exact FOV dimensions with our sales engineers**

## NOTES

- Working distance: distance between the front end of the mechanics and the object. Set this distance within +/- 3% of the nominal value for maximum resolution and minimum distortion.
- Working F-number (wF/#): the real F-number of a lens when used as a macro. Lenses with smaller apertures can be supplied on request.
- Maximum slope of chief rays inside the lens: when converted to millirad, it gives the maximum measurement error for any millimeter of object displacement. Typical (average production) values and maximum (guaranteed) values are listed.
- Percent deviation of the real image compared to an ideal, undistorted image: typical (average production) values and maximum (guaranteed) values are listed.
- At the borders of the field depth the image can be still used for measurement but, to get a perfectly sharp image, only half of the nominal field depth should be considered. Pixel size used for calculation is 5.5  $\mu\text{m}$ .
- In case the of vignetting, FOV dimensions are indicated with " $\varnothing$  = ", x= ", where " $\varnothing$  =" stands for diameter and "x=" indicates the nominal FOV height and length (see [Tech Info](#) for related drawing).
- Indicates the availability of an integrated camera phase adjustment feature.
- Due to the special shape of TCCR120xx it might be necessary to check the mechanical compatibility with your camera.
- Indicates the dimensions and shape of image, where " $\varnothing$  =" stands for diameter and "x=" indicates the nominal image height and length ([Tech Info](#) for related drawing).

## COMPATIBLE PRODUCTS





LTCLHP120-R	Telecentric HP illuminator, beam diameter 150 mm, red
LTCLHP120-G	Telecentric HP illuminator, beam diameter 150 mm, green
LTCLHP120-W	Telecentric HP illuminator, beam diameter 150 mm, white



LTCLCR120-R	Telecentric CORE illuminator, beam dimensions Ø = 156, x = 130, red, 630 nm
LTCLCR120-G	Telecentric CORE illuminator, beam dimensions Ø = 156, x = 130, green, 520 nm
LTCLCR120-W	Telecentric CORE illuminator, beam dimensions Ø = 156, x = 130, white