



Hirose Pinout		EXO, HR (CL Deca, CXP), SHR
Pin	Signal	EXO, HR (CL Deca, CXP), SHR
1	V IN- (GND)	
2	V IN+ (10 - 25V)	
3	IN 4 RxD (RS232)	
4	OUT 4 TxD (RS232)	
5	IN 1 (0 - 24V)	
6	IN 2 (0 - 24V)	
7	OUT 1 (open drain)	
8	OUT 2 (open drain)	
9	IN 3+ (opto IN+)	
10	IN 3- (opto IN-)	
11	OUT 3 (open drain)	
12	OUT 0 (open drain)	
Shielding		

- drawing applies to mono and color cameras
- FXO425x25GE
 - FXO530x25GE
 - FXO531x25GE
 - FXO532x25GE
 - FXO535x25GE
 - FXO536x25GE
 - FXO537x25GE

 High-Speed Vision Solutions	all dimensions in mm unless otherwise specified	Scale: 1:1 Rev.: 1
	Customer Interface Drawing	
Title: FXO425,530,531,532,535,536,537X25GE		Material No.:
Drawn: S.Seller Checked: ---	Name: S.Seller Sign: --- Date: 21.09.2023	Material:
Weight:		A2 Blatt/Sheet 1 / 1